

IMPROVED POLYURETHANE/GEOTEXTILE COMPOSITE AND  
A PROCESS RELATED THERETO FOR THE PRODUCTION THEREOF

ABSTRACT OF THE DISCLOSURE

A polyurethane/geotextile composite having greater strength and dimensional stability than composites made with filled polyurethanes is produced by impregnating a geotextile with an unfilled polyurethane composition and allowing the polyurethane composition to cure. The polyurethane composition employed is reaction product of a liquid polyisocyanate having an isocyanate content of at least 10% by weight, a high molecular weight polyether polyol, and an organometallic catalyst. A low molecular weight diol or triol may optionally be included in the polyurethane-forming reaction mixture. These polyurethane/geotextile composites are particularly suitable for lining ditches and canals.

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100